

CP6613 - The most robust pneumatic nutrunner in its class with 960 ft.lbs / 1,300 Nm max.



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm
- ▶ Lightweight

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6613	
Part number	6151800090	
Square drive	3/4"	19 mm
Length	254 mm	10"
Net weight	3.7 kg	8.3 lb
Height	212 mm	8.34"
Width	72 mm	2.83"
Side to center	32 mm	1.26"
Free speed air consumption	23 l/s	48 cfm
Min. hose size	13 mm	1/2"
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s ²	

Reaction bar	S-type	
Reversible	Reversible	
Torque preset #	Multi	
Square drive	3/4"	19
Handle type	Pistol	
Free speed	20 rpm	
Working Torque Range (fwd)	320 - 1300 Nm	236 - 960
Working Torque Range (reverse)	320 - 1300 Nm	236 - 960
Maximum Torque (fwd)	1300 Nm	960 <i>ft.lbs</i>
Maximum Torque (reverse)	1300 Nm	960 <i>ft.lbs</i>
Socket retainer	Hole	
Square drive	19 mm	3/4"
Bolt size	20-27	3/4 - 1-1/16
European Directives	2006/42/EC (17/05/2006)	
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	4.4 kg	10.1 <i>lb</i>
Weight w/o Reaction Arm	3.7 kg	8.3 <i>lb</i>

CP6613 + ATC PACK - The most robust pneumatic nutrunner in its class with 960 ft.lbs / 1,300 Nm max. and our most accurate air supply solution



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm
- ▶ Lightweight

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6613 + ATC PACK	
Part number	6151800120	
Square drive	3/4"	19 mm
Length	254 mm	10"
Height	212 mm	8.34"
Width	72 mm	2.83"
Side to center	32 mm	1.26"
Free speed air consumption	23 l/s	48 cfm
Min. hose size	13 mm	1/2"
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s ²	

European Directives	2006/42/EC (17/05/2006)	
European Standards	EN ISO 11148-6:2012	
Reaction bar	S-type	
Reversible	Reversible	
Torque preset #	Multi	
Square drive	3/4"	19
Handle type	Pistol	
Free speed	20 rpm	
Working Torque Range (fwd)	320 - 1300 Nm	236 - 960
Working Torque Range (reverse)	320 - 1300 Nm	236 - 960
Maximum Torque (fwd)	1300 Nm	960 <i>ft.lbs</i>
Maximum Torque (reverse)	1300 Nm	960 <i>ft.lbs</i>
Socket retainer	Hole	
Square drive	19 mm	3/4"
Bolt size	20-27	3/4 - 1-1/16
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	4.4 kg	10.1 <i>lb</i>
Weight w/o Reaction Arm	3.7 kg	8.3 <i>lb</i>

CP6626 + ATC PACK - The most robust pneumatic nutrunner in its class with 1,900 ft.lbs / 2,600 Nm max. and our most accurate air supply solution



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description	
Model	CP6626 + ATC PACK
Part number	6151800130
Length	300 mm 12"
Height	212 mm 8.34"
Width	72 mm 2.32"
Side to center	34 mm 1.34"
Sound pressure	90 db(A)
Sound Power	101 db(A)
European Sound standard	ISO 15744
Sound uncertainty	3 db(A)
Vibration ISO	ISO 28927-2
Vibration	<2,5 m/s ²
European Directives	2006/42/EC (17/05/2006)
European Standards	EN ISO 11148-6:2012
Reaction bar	S-type
Reversible	Reversible

Torque preset #	Multi	
Square drive	1"	25 mm
Handle type	Pistol	
Free speed	10 rpm	
Working Torque Range (fwd)	700 - 2600 Nm	520 - 1900
Working Torque Range (reverse)	700 - 2600 Nm	520 - 1900
Maximum Torque (fwd)	2600 Nm	1900 ft.lbs
Maximum Torque (reverse)	2600 Nm	1900 ft.lbs
Socket retainer	Hole	
Square drive	25 mm	1"
Bolt size	20 - 36	3/4 - 1 3/8
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	6.5 kg	14.3 lb
Weight w/o Reaction Arm	5.1 kg	11.2 lb

CP6626 - The most robust pneumatic nutrunner in its class with 1,900 ft.lbs / 2,600 Nm max.



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6626	
Part number	6151800100	
Length	300 mm	12"
Net weight	5.1 kg	11.2 lb
Height	212 mm	8.34"
Width	72 mm	2.83"
Side to center	34 mm	1.34"
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s ²	
European Directives	2006/42/EC (17/05/2006)	
European Standards	EN ISO 11148-6:2012	
Reaction bar	S-type	

Reversible	Reversible	
Torque preset #	Multi	
Square drive	1"	25 mm
Handle type	Pistol	
Free speed	10 rpm	
Working Torque Range (fwd)	700 - 2600 Nm	520 - 1900
Working Torque Range (reverse)	700 - 2600 Nm	520 - 1900
Maximum Torque (fwd)	2600 Nm	1900 ft.lbs
Maximum Torque (reverse)	2600 Nm	1900 ft.lbs
Socket retainer	Hole	
Square drive	25 mm	1"
Bolt size	20 - 36	3/4 - 1 3/8
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	6.5 kg	14,3 lb
Weight w/o Reaction Arm	5.1 kg	11.2 lb

CP6641 + ATC PACK - The most robust pneumatic nutrunner in its class with 3,100 ft.lbs / 4,100 Nm max. and our most accurate air supply solution



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6641 + ATC PACK	
Part number	6151800140	
Length	361 mm	14.21"
Height	228 mm	8.97"
Width	100 mm	3.94"
Side to center	40 mm	1.57"
Average air consumption	23 l/s	
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s ²	
European Directives	2006/42/EC (17/05/2006)	
European Standards	EN ISO 11148-6:2012	
Reaction bar	S-type	

Reversible	Reversible	
Torque preset #	Multi	
Square drive	1"	25 mm
Handle type	Pistol	
Free speed	10 rpm	
Working Torque Range (fwd)	1000 - 4100 Nm	738 - 3100
Working Torque Range (reverse)	1000 - 4100 Nm	738 - 3100
Maximum Torque (fwd)	4100 Nm	3100 ft.lbs
Maximum Torque (reverse)	4100 Nm	3100 ft.lbs
Socket retainer	Hole	
Square drive	25 mm	1"
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	10.8 kg	23.8 lb
Weight w/o Reaction Arm	8.8 kg	19.4 lb

CP6641 - The most robust pneumatic nutrunner in its class with 3,100 ft.lbs / 4,100 Nm max.



Benefits

- ▶ Robust
- ▶ Accurate
- ▶ Strong lightweight reaction arm

Features

- ▶ Replaceable protective cover
- ▶ Reliable Gearbox: 13,000 cycles before maintenance
- ▶ Vane type high performance air motor same as industrial impact wrench
- ▶ Capable of reaching high torque accuracy
- ▶ Different reaction arm types and shapes available
- ▶ Reduce operator fatigue and risks of MSDs

Technical description		
Model	CP6641	
Part number	6151800110	
Length	361 mm	14.21"
Net weight	8.8 kg	19.4 lb
Height	228 mm	8.97"
Width	100 mm	3.94"
Side to center	40 mm	1.57"
Average air consumption	23 l/s	
Sound pressure	90 db(A)	
Sound Power	101 db(A)	
European Sound standard	ISO 15744	
Sound uncertainty	3 db(A)	
Vibration ISO	ISO 28927-2	
Vibration	<2,5 m/s ²	
Vibration uncertainty (K)	/ m/s ²	
European Directives	2006/42/EC (17/05/2006)	

European Standards	EN ISO 11148-6:2012	
Reaction bar	S-type	
Reversible	Reversible	
Torque preset #	Multi	
Square drive	1"	25 mm
Handle type	Pistol	
Free speed	10 rpm	
Working Torque Range (fwd)	1000 - 4100 Nm	738 - 3100
Working Torque Range (reverse)	1000 - 4100 Nm	738 - 3100
Maximum Torque (fwd)	4100 Nm	3100 ft.lbs
Maximum Torque (reverse)	4100 Nm	3100 ft.lbs
Socket retainer	Hole	
Square drive	25 mm	1"
Sound DBA pressure	90 db(A)	
European Standards	EN ISO 11148-6:2013	
Weight Including Reaction Arm	10.8 kg	23.8 lb
Weight w/o Reaction Arm	8.8 kg	19.4 lb