




CP7600C-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>
- ▶ Short version with CUPS reaction bar in option

Technical description		
Model	CP7600C-R	
Part number	8941076031	
Length	345 mm	13.6"
Net weight	7.4 kg	16.3 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
European Directives	2006/42/EC	
European Standards	EN ISO 11148-6:2012	
Reaction bar	C reaction bar	
Reversible	Reversible	
Torque preset #	1	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	

CP7600C-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²
- ▶ Short version with CUPS reaction bar in option

Technical description		
Model	CP7600C-R4P	
Part number	8941076035	
Length	380 mm	15"
Net weight	7.7 kg	17 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
European Directives	2006/42/EC	
European Standards	EN ISO 11148-6:2012	
Reaction bar	C reaction bar	
Reversible	Reversible	
Torque preset #	4	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	

CP7600xB-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²

Technical description		
Model	CP7600xB-R4P	
Part number	8941076015	
Length	380 mm	15"
Net weight	6.9 kg	15.2 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
European Directives	2006/42/EC	
European Standards	EN ISO 11148-6:2012	
Reaction bar	xB reaction bar	
Reversible	Reversible	
Torque preset #	4	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	



CP7600xB-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Operator's comfort for more productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>

Technical description		
Model	CP7600xB-R	
Part number	8941076011	
Length	345 mm	13.6"
Net weight	6.6 kg	14.6 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
European Directives	2006/42/EC	
European Standards	EN ISO 11148-6:2012	
Reaction bar	xB reaction bar	
Reversible	Reversible	
Torque preset #	1	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	



CP7600xB - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Increased operator comfort for greater productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>



Technical description		
Model	CP7600xB	
Part number	8941076010	
Length	328 mm	12.9"
Net weight	6 kg	13.2 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
European Directives	2006/42/EC	
European Standards	EN ISO 11148-6:2012	
Reaction bar	xB reaction bar	
Reversible	Non reversible	
Torque preset #	1	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	

CP7600xC-R4P - Our most ergonomic & efficient solution for trucks and buses wheel maintenance



Benefits

- ▶ Selection Up to 4 calibrated tightening Torque
- ▶ Accurate torque
- ▶ Operator's comfort for more productivity
- ▶ Fast rundown

Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <2,5 m/s²
- ▶ Extended version with included spring load cup reaction bar



Technical description		
Model	CP7600xC-R4P	
Part number	8941076025	
Length	495 mm	19.5"
Net weight	9.1 kg	20.1 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
Reaction bar	xC reaction bar	
Reversible	Reversible	
Torque preset #	4	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	

CP7600xC-R - Our most ergonomic & efficient solution for trucks and buses wheel maintenance

Benefits

- ▶ Selection Up to 4 calibrated tightening Torque .
- ▶ Accurate torque.
- ▶ Operator's comfort for more productivity.
- ▶ Fast rundown.



Features

- ▶ Air Shut-off clutch at preset torque
- ▶ Integrated reaction bar standard with blade
- ▶ Low noise level: 79 dB(A)
- ▶ Almost no vibration : <math><2,5 \text{ m/s}^2</math>
- ▶ Extended version with included spring load cup reaction bar



Technical description		
Model	CP7600xC-R	
Part number	8941076021	
Length	460 mm	18.1"
Net weight	8.8 kg	19.4 lb
Free speed air consumption	19 l/s	40 cfm
Sound pressure	79 db(A)	
Sound Power	90 db(A)	
Vibration ISO	ISO-28927-2	
Reaction bar	xC reaction bar	
Reversible	Reversible	
Torque preset #	1	
Square drive	1"	
Handle type	Pistol	
Free speed	100 rpm	
Working Torque Range (fwd)	450 - 900 Nm	330 - 660
Working Torque Range (reverse)	450 - 900 Nm	330 - 660
Maximum Torque (fwd)	900 Nm	660 ft.lbs
Maximum Torque (reverse)	900 Nm	660 ft.lbs
Socket retainer	Hole	